


## Full HD 1080p Indoor/Outdoor Vandal Resistant Dome IP Camera

**O2D4** 3.6-16mm auto iris varifocal lens, dark grey housing

### Features

- Supports up to Full HD 1080p @ 30fps
- Built-in standard PoE (IEEE 802.3af)
- True Day/Night operation (IR cut filter)
- Built-in IR LEDs
- IR Range: 49' (depending on scene reflection)
- Chameleon Cover™: snaps on and can be painted to match any décor!\*
- Wide dynamic range (WDR) operation
- Supports H.264 and MJPEG codecs
- 2-way audio communication
- Micro SD card slot (card not included)
- IP66 and IK08 compliant
- Conformant with ONVIF profile S\*
- 2 year warranty



Shown with included paintable, snap-on Chameleon Cover™

### Camera Specifications

Image Sensor ..... Progressive scan 1/2.9" CMOS, 2MP  
 Maximum Resolution ..... 1920x1080  
 Minimum Illumination ..... F1.4, 0.12 lux (IR on – 0 lux)  
 IR LEDs ..... 18  
 IR Range ..... 49' (depending on scene reflection)  
 White Balance ..... Automatic  
 Exposure Control ..... Yes  
 Digital Slow Shutter ..... Yes  
 WDR/BLC ..... WDR  
 Day/Night ..... IR-cut filter  
 DNR ..... 2D/3D

### Video Specifications

Supported Resolutions .. 1920x1080 @ 30fps / 1280x720 @ 30fps  
 Compression ..... H.264 (HP/MP/BP), MJPEG  
 Bitrate Control ..... VBR, CBR  
 Multiple Streaming ..... 5 simultaneous profiles

### Audio Specifications

Mono Input ..... 64Kbps G.711 / 32Kbps G.726  
 Mono Output ..... 64Kbps G.711

### External Terminal Specifications

Ethernet ..... 10/100 Mbps  
 Alarm ..... 1 sensor input, 1 output  
 Video ..... Analog test output  
 Audio ..... 1 mic in, 1 line out (3.5mm)  
 Power ..... DC jack  
 Storage ..... Micro SD slot

### Network Specifications

Protocols ..... IPv4, IPv6, TCP, UDP, RTP, RTSP, HTTP, HTTPS, SMTP, FTP, DHCP, UPnP, NTP, DNS

### Network Specifications (continued)

DDNS support ..... Speco DDNS (free of charge)  
 Security ..... User ID & Password protection, IP address filtering, HTTPS, digest authentication, user access log  
 User Access ..... 8 simultaneous users at D1 resolution  
 Number of users may vary depending on resolution

### System Specifications

PoE ..... Standard (IEEE 802.3af)  
 Analytics ..... Motion detection (3 regions), audio detection  
 Alarm Triggers ..... Analytics & sensor input  
 Alarm Events ..... FTP video file upload, email image upload, micro SD card recording, alarm out  
 Video Buffer ..... Configurable pre-record & post-record  
 Image Settings ..... Text overlay, privacy mask

### Client Specifications

Web Browser Support ... Windows (Internet Explorer 8 and up, Chrome and Firefox\*\*)  
 Mobile Apps ..... Speco OnSIP (iPhone®, iPad® and Android™)  
 PC Application ..... Speco NVR, SecureGuard®

### Operating & Unit Specifications

Power Supply ..... PoE, 12VDC (power supply not included)  
 Power Consumption ..... 6W with IR  
 Operating Temperature .. -4° F – 122° F  
 Operating Humidity ..... 8% – 80% RH  
 Unit Dimensions ..... 3.62" (H) x 5.11" (Dia.)  
 Unit Weight ..... 2 lbs.  
 Certifications ..... FCC, RoHS  
 Included in Package ..... Unit, CD (manual, software), mounting screws, L wrench

### Optional Accessories



\*Visit [www.specotech.com/onvif.html](http://www.specotech.com/onvif.html) for latest ONVIF® support. ONVIF is a trademark of Onvif, Inc. \*\*Chrome and Firefox use Java which requires an initial internet connection. Apple and the Apple logo are trademarks of Apple Inc., registered in the U.S. and other countries. App Store is a service mark of Apple Inc. Android, Google Play and the Google Play logo are trademarks of Google Inc. Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation. Spec Rev. 1/20/16